

## Defender Range

Portable welding frames & bespoke booths and curtains

The necessary solution for employee protection.

WELDING CURTAINS



Offering all the same benefits as the Defender 100, but manufactured with a sturdier and heavier grade frame – 30mm OD and 4kgs heavier. The solid 1 piece curtain is attached through both a top and bottom rail.

These screens adhere to EN1598 welding standard, therefore offering all the necessary requirements to achieve a safe welding environment.

STOCK COLOUR	RED
OUTER FRAME DIMENSIONS	1460MM (4FT 8") W X 1900MM (6FT 3") H
FRAME TYPE	32.9MM DIAMETER POWDER COATED STEEL TUBE FRAME
PVC CURTAIN DIMENSIONS	1415MM (4FT 6") W X 1580MM (5FT1") H
CURTAIN FROM FLOOR	320MM
PVC CURTAIN THICKNESS	0.4MM EN1598
OUTER CARTON	1720MM L X 265MM D X 100MM H



Certificate Number: 14352  
ISO 9001



Care should be taken in selecting the most suitable quality for each application. Advice is available, but final responsibility remains with the customer.

[www.epdm.co.uk](http://www.epdm.co.uk)

E-Mail: [Sales@epdm.co.uk](mailto:Sales@epdm.co.uk)

### Contact

Telephone: +44 (0)1625 573971

FAX: +44(0)1625 573250

PTM Ltd

Units AG2/3 Clarence Mill

Clarence Road, Bollington

Macclesfield, Cheshire

SK10 5JZ

United Kingdom