

Technical Data Sheet

EOLO Pu Food

- ✓ Ether based food grade TPU wall, with antishock rigid PVC spiral
- ✓ Smooth inside, corrugated outside
- ✓ Excellent resistance to abrasion and hydrolysis
- ✓ Resistant to most chemicals
- ✓ Very light weight and flexible



FDA Reg. Cfr.21-Item 17.2600 (aqueous and fatty food) Reg. EU 10/2011, classes A, B, C, D2



Hose & Ducting



Certificate Number: 14362
ISO 9001



Care should be taken in selecting the most suitable quality for each application. Advice is available, but final responsibility remains with the customer.

Web: www.epdm.co.uk

E-Mail: Sales@epdm.co.uk

Contact

Telephone: +44 (0)1625 573971

FAX: +44(0)1625 573250

PTM Ltd

Units AG2/3 Clarence Mill

Clarence Road, Bollington

Macclesfield, Cheshire

SK10 5JZ

United Kingdom

Hose & Ducting

Part number	Ø Ins.	Min. wall thick.	Max wall thick.	Weight	Vac.	Bending r.	Coil lgth.	Volume
	mm	mm	m	g/m	mH2O	mm	m	m ³
EU 01 020.0 000.0	20	0,4	2,5	115	2,5	25	20	0,028
EU 01 025.0 000.0	25	0,4	2,6	140	2,5	30	20	0,035
EU 01 030.0 000.0	30	0,4	2,6	160	2,5	35	20	0,049
EU 01 032.0 000.0	31,8	0,4	2,6	180	2	35	20	0,051
EU 01 035.0 000.0	35	0,5	2,7	200	2	45	20	0,059
EU 01 038.0 000.0	38,1	0,5	2,8	220	2	50	20	0,068
EU 01 040.0 000.0	40	0,5	2,8	230	2	60	20	0,071
EU 01 045.0 000.0	45	0,5	2,9	270	2	65	20	0,083
EU 01 052.0 000.0	50,8	0,5	3,2	320	2	70	20	0,104
EU 01 055.0 000.0	55	0,5	3,4	400	2	75	20	0,119
EU 01 060.0 000.00	60	0,5	3,6	470	1,6	80	20	0,170
EU 01 063.0 000.0	63,5	0,5	3,6	510	1,6	80	20	0,180
EU 01 065.0 000.0	65	0,5	3,6	520	1,6	90	20	0,191
EU 01 070.0 000.0	70	0,6	3,9	550	1,6	95	30	0,293
EU 01 076.0 000.0	76,2	0,6	3,9	600	1,6	100	30	0,328
EU 01 080.0 000.0	80	0,6	4,2	650	1,6	110	30	0,357
EU 01 090.0 000.0	90	0,6	4,3	750	1,4	125	30	0,547
EU 01 100.0 000.0	100	0,6	4,4	820	1,3	140	30	0,640
EU 01 102.0 000.0	102	0,6	4,4	830	1,3	140	30	0,652
EU 01 110.0 000.0	110	0,6	4,7	950	1,2	150	30	0,743
EU 01 120.0 000.0	120	0,6	5,0	1100	1	160	30	0,831
EU 01 127.0 000.0	127	0,6	5,0	1150	1	170	30	0,900
EU 01 130.0 000.0	130	0,7	5,3	1300	0,9	170	20	0,780
EU 01 140.0 000.0	140	0,7	5,3	1430	0,9	180	20	0,860
EU 01 150.0 000.0	151,5	0,7	5,3	1500	0,8	200	20	0,953
EU 01 160.0 000.0	160	0,7	6,7	1940	0,7	220	20	1,049
EU 01 180.0 000.0	180	0,7	6,7	2140	0,4	250	20	1,236
EU 01 200.0 000.0	200	0,7	6,7	2300	0,4	260	20	1,440
EU 01 250.0 000.0	250	0,8	7,5	3400	0,4	300	10	0,952
EU 01 300.0 000.0	300	0,8	7,7	4100	0,3	350	10	1,419

Also available in an Anti-static Version.



Certificate Number: 14362
ISO 9001



Care should be taken in selecting the most suitable quality for each application. Advice is available, but final responsibility remains with the customer.

Web: www.epdm.co.uk

E-Mail: Sales@epdm.co.uk

Contact

Telephone: +44 (0)1625 573971

FAX: +44(0)1625 573250

PTM Ltd

Units AG2/3 Clarence Mill

Clarence Road, Bollington

Macclesfield, Cheshire

SK10 5JZ

United Kingdom