

## Technical Data Sheet

### Hermes Clear Braided PVC

Hose & Ducting



#### Product Information










Order Ref: STANDARD - CBP-IZE  
-MM / HEAVY - HDCBP-SIZE-MM

Tube: TRANSPARENT PLASTICIZED PVC, LOW TOXIC ODOURLESS PVC

Reinforcement: HIGH TENSILE POLYESTER FIBRES

Cover: ABRASION, OZONE AND WEATHER RESISTANT TRANSPARENT PVC

Application: LIGHT DUTY HOSE FOR MULTIPURPOSE USE, GENERAL WATER DISCHARGE AND LOW PRESSURE AIR LINES. SUITABLE FOR FOOD AND WATER

									
Inch	mm	mm	BAR	PSI	BAR	PSI	mm	gr/mt	mt
STANDARD DUTY									
1/4	6.3	10.5	10	150	30	450	30	73	30
5/16	8	12	10	150	30	450	40	80	30
3/8	10	14	10	150	30	450	50	99	30
1/2	12.5	17.5	10	150	30	450	60	152	30
5/8	15.9	21	10	150	30	450	80	197	30
3/4	19	24	10	150	30	450	95	240	30
1	25	31	10	150	30	450	125	367	30
1 1/4	32	40	10	150	30	450	208	576	30
1 1/2	38	46	10	150	30	450	247	632	30
2	50	60	10	150	30	450	325	1104	30



Certificate Number: 14352  
ISO 9001



Care should be taken in selecting the most suitable quality for each application. Advice is available, but final responsibility remains with the customer.

Web: [www.epdm.co.uk](http://www.epdm.co.uk)

E-Mail: [Sales@epdm.co.uk](mailto:Sales@epdm.co.uk)

#### Contact

Telephone: +44 (0)1625 573971

FAX: +44(0)1625 573250

PTM Ltd

Units AG2/3 Clarence Mill

Clarence Road, Bollington

Macclesfield, Cheshire

SK10 5JZ

United Kingdom

# Hose & Ducting

HEAVY DUTY									
1/4	6.3	11.4	14.25	210	57	840	92		30
5/16	8	13.2	12.25	180	49	720	101		30
3/8	9.25	16	11.25	165	45	660	112		30
1/2	12.5	18.2	10.5	154	42	616	152		30
5/8	15.9	23	10	150	40	600	161		30
3/4	19	25.6	10	150	40	600	177		30
1	25	32.6	10	150	40	600	254		30



Branding:

-15°C to +60°C

HERMES - NON TOXIC - SIZE

Colour:

CLEAR - AVAILABLE IN OTHER COLOURS PLEASE CONTACT SALES OFFICE



Certificate Number: 14352  
ISO 9001



Care should be taken in selecting the most suitable quality for each application. Advice is available, but final responsibility remains with the customer.

**Web: [www.epdm.co.uk](http://www.epdm.co.uk)**

**E-Mail: [Sales@epdm.co.uk](mailto:Sales@epdm.co.uk)**

#### Contact

Telephone: +44 (0)1625 573971

FAX: +44(0)1625 573250

PTM Ltd

Units AG2/3 Clarence Mill

Clarence Road, Bollington

Macclesfield, Cheshire

SK10 5JZ

United Kingdom