

Technical Data Sheet

Multipurpose Hose

Product Information



Flexible PVC/NBR hose reinforced with a braided Polyester yarn

For applications that require a flexible and oil-resistant hose

Temperature range -20°C to +80°C

Part number	Ø ins	Ø out	Weight	WP	Bending R.	Coil Lgth.	Vol.
	[mm]	[mm]	[g/m]	[bar]	[mm]	[m]	[m³]
MP 01 006.0 013.0	6	13	146	20	30	100	0.025
MP 01 008.0 015.0	8	15	177	20	40	100	0.030
MP 01 010.0 017.0	10	17	208	20	50	100	0.041
MP 01 013.0 020.0	13	20	254	20	70	100	0.065
MP 01 016.0 023.0	16	23	300	20	80	100	0.100
MP 01 019.0 028.0	19	28	465	20	100	100	0.126
MP 01 025.0 034.0	25	34	584	20	130	100	0.220

Hose & Ducting



Certificate Number: 14352
ISO 9001



Care should be taken in selecting the most suitable quality for each application. Advice is available, but final responsibility remains with the customer.

Web: www.epdm.co.uk

E-Mail: Sales@epdm.co.uk

Contact

Telephone: +44 (0)1625 573971

FAX: +44(0)1625 573250

PTM Ltd

Units AG2/3 Clarence Mill

Clarence Road, Bollington

Macclesfield, Cheshire

SK10 5JZ

United Kingdom