

Technical Data Sheet

Zeuss Pu Food

Heavy duty product with a PU wall thickness from 1.2 up to 2 mm resistant to abrasion and flexion, this hose features high mechanical properties. Excellent resistance to microbes, hydrolysis, ozone, weather conditions, most chemicals. Halogens free and conform to RoHS as well as free from phthalates. Food grade according to FDA Reg Cfr 21-Item 17.2600 (aqueous and fatty food). Commonly used with abrasives, and in the plastics and food & beverage industries.

Hose & Ducting



Certificate Number: 14362
ISO 9001



Care should be taken in selecting the most suitable quality for each application. Advice is available, but final responsibility remains with the customer.

Web: www.epdm.co.uk

E-Mail: Sales@epdm.co.uk

Contact

Telephone: +44 (0)1625 573971

FAX: +44(0)1625 573250

PTM Ltd

Units AG2/3 Clarence Mill

Clarence Road, Bollington

Macclesfield, Cheshire

SK10 5JZ

United Kingdom

Hose & Ducting

Part number	Ø Ins.	Min Wall thick	Max Wall thick	weight	WP	BP	Vac.	Bending r.	Coil lgth.	Vol.
	mm	Mm	mm	g/m	bar	bar	mH2O	mm	m	m3
ZE 01 030.0 000.0	30	1,2	3,4	320	3,0	9	9	130	30	0,090
ZE 01 032.0 000.0	31,8	1,2	3,4	340	3,0	9	9	140	30	0,099
ZE 01 035.0 000.0	35	1,3	3,6	380	3,0	9	9	160	30	0,108
ZE 01 038.0 000.0	38,1	1,3	3,8	410	3,0	9	9	180	30	0,117
ZE 01 040.0 000.0	40	1,5	4,6	490	3,0	9	9	190	30	0,139
ZE 01 045.0 000.0	45	1,5	4,7	570	3,0	9	8	200	30	0,154
ZE 01 052.0 000.0	50,8	1,5	5,2	700	3,0	9	8	215	30	0,214
ZE 01 060.0 000.0	60	1,5	5,2	870	3,0	9	8	230	30	0,246
ZE 01 063.0 000.0	63,5	1,5	5,2	910	3,0	9	8	240	30	0,298
ZE 01 065.0 000.0	65	1,5	5,2	930	3,0	9	8	240	30	0,304
ZE 01 070.0 000.0	70	1,5	5,2	940	2,5	7,5	8	250	30	0,371
ZE 01 076.0 000.0	76,2	1,7	5,2	1120	2,5	7,5	8	270	30	0,466
ZE 01 080.0 000.0	80	2,0	5,3	1260	2,5	7,5	7	290	30	0,518
ZE 01 090.0 000.0	90	2,0	5,3	1400	2,5	7,5	7	380	30	0,592
ZE 01 100.0 000.0	100	2,0	6,0	1600	2,5	7,5	7	420	30	0,716
ZE 01 102.0 000.0	102	2,0	6,0	1630	2,5	7,5	7	420	30	0,729
ZE 01 120.0 000.0	120	2,0	7,0	2400	2,0	6	6,5	480	30	1,544
ZE 01 127.0 000.0	127	2,0	7,0	2500	1,5	4,5	6,5	530	30	1,625
ZE 01 150.0 000.0	151,5	2,0	7,5	3100	1,5	4,5	6	800	20	1,279



Certificate Number: 14362
ISO 9001



Care should be taken in selecting the most suitable quality for each application. Advice is available, but final responsibility remains with the customer.

Web: www.epdm.co.uk

E-Mail: Sales@epdm.co.uk

Contact

Telephone: +44 (0)1625 573971

FAX: +44(0)1625 573250

PTM Ltd

Units AG2/3 Clarence Mill

Clarence Road, Bollington

Macclesfield, Cheshire

SK10 5JZ

United Kingdom