

Technical Data Sheet

Mercury Air 20

Premium Rubber 20 Bar Air Hose ISO2398-4A










Hose & Ducting



Product Information

Order Ref: RAH-SIZE MM
 Tube: SYNTHETIC RUBBER INNER
 Reinforcement: HIGH TENSILE SYNTHETIC TEXTILE
 Cover: ABRASION, OZONE AND WEATHER RESISTANT SMOOTH NATURAL AND SYNTHETIC RUBBER
 Application: MEDIUM DUTY SERVICE FOR AIR AND PNEUMATIC TOOLS SPECIFICALLY IN MINES, QUARRIES AND CONSTRUCTION

Specification: TS 745 / EN ISO 2398 TYPE 4/A

									
Inch	mm	Mm	BAR	PSI	BAR	PSI	Mm	gr/mt	Mt
1/4	6	13	20	290	60	870	60	130	25/100
5/16	8	16	20	290	60	928	80	190	25/100
3/8	10	18	20	290	60	870	100	230	25/50/100
1/2	13	22	20	290	60	870	130	333	25/50/100
3/4	19	30	20	290	60	928	190	580	25/50
1	25	36	20	290	60	870	250	730	25/50



-40°C to +70°C

Branding:

MERCURY 20 AIR/WP 20BAR ISO2398 4A-SIZE QTR/YR

Colour:

Black



Certificate Number: 14352
ISO 9001



Care should be taken in selecting the most suitable quality for each application. Advice is available, but final responsibility remains with the customer.

Web: www.epdm.co.uk

E-Mail: Sales@epdm.co.uk

Contact

Telephone: +44 (0)1625 573971

FAX: +44(0)1625 573250

PTM Ltd

Units AG2/3 Clarence Mill

Clarence Road, Bollington

Macclesfield, Cheshire

SK10 5JZ

United Kingdom