

Technical Data Sheet










Mercury Air 20 Premium Rubber 20 Bar Air Yellow

Hose & Ducting



Product Information

Order Ref: RAY-SIZE MM
 Tube: SYNTHETIC RUBBER INNER
 Reinforcement: HIGH TENSILE SYNTHETIC TEXTILE
 Cover: ABRASION, OZONE AND WEATHER RESISTANT SMOOTH NATURAL AND SYNTHETIC RUBBER
 Application: MEDIUM DUTY SERVICE FOR AIR AND PNEUMATIC TOOLS SPECIFICALLY IN MINES, QUARRIES AND CONSTRUCTION
 Specification: TS 745 / EN ISO 2398 TYPE 4/A

									
Inch	mm	Mm	BAR	PSI	BAR	PSI	Mm	gr/mt	Mt
3/8	10	18	20	290	60	870	100	220	100
1/2	13	22	20	290	60	870	130	270	100
3/4	19	30	20	290	60	928	190	570	60
1	25	36	20	290	60	870	250	800	60



Branding:
Colour:

-25°C to +70°C
 MERCURY 20 AIR/WP 20BAR ISO2398 4A-SIZE QTR/YR
 Yellow



Certificate Number: 14352
ISO 9001



Care should be taken in selecting the most suitable quality for each application. Advice is available, but final responsibility remains with the customer.

Web: www.epdm.co.uk
 E-Mail: Sales@epdm.co.uk

Contact

Telephone: +44 (0)1625 573971
 FAX: +44(0)1625 573250
 PTM Ltd
 Units AG2/3 Clarence Mill
 Clarence Road, Bollington
 Macclesfield, Cheshire
 SK10 5JZ
 United Kingdom