

## Technical Data Sheet

**MATERIAL PROPERTIES\*:** Novus Ti (Tanged)

**DESCRIPTION:** Novus TI is a graphite laminate product reinforced with an insertion of tanged 0.10mm thick 316 stainless steel. No adhesive is required to bond the graphite layers to the tanged insert resulting in a sturdy gasket material with excellent mechanical strength.

**COLOUR:** Grey/Black

**SERVICE:** Novus TI is used throughout industry in pipeline and vessel applications. Its wide temperature range and excellent stress retention make it ideal for steam systems and process duties in the petrochemical and manufacturing industries.



**PHYSICAL PROPERTIES:**

Thickness		1.5mm
Density		1.0g/cm3
No. of Inserts		1
Ash Content Max		2%
Chloride Content		Max 50ppm
Compressibility	ASTM F36A	30-35%
Recovery	ASTM F36A	15-20%
Residual Stress	DIN 52913 (300°C)	>48 MPa
ASME m Factor		2.5
y Value		3000psi

**AVAILABILITY:**

Thickness range: 1.0mm to 3.0mm  
 Standard sheet size: 1.5m x 1.5m

Notes: \* This is a general guide and should not be the sole means of selecting or rejecting this material. This data sheet covers basic information, for more comprehensive information, please contact us.

**Asbestos Free**



Certificate Number: 14352  
 ISO 9001



Care should be taken in selecting the most suitable quality for each application. Advice is available, but final responsibility remains with the customer.

**Web: [www.epdm.co.uk](http://www.epdm.co.uk)**  
**E-Mail: [Sales@epdm.co.uk](mailto:Sales@epdm.co.uk)**

**Contact**

Telephone: +44 (0)1625 573971  
 FAX: +44 (0)1625 573250  
 Munsch & Co/PTM Ltd  
 Units AG2/3 Clarence Mill  
 Clarence Road, Bollington  
 Macclesfield, Cheshire  
 SK10 5JZ  
 United Kingdom