

Technical Data Sheet

EOLO Pu Food

- ✓ Ether based food grade TPU wall, with antishock rigid PVC spiral
- ✓ Smooth inside, corrugated outside
- ✓ Excellent resistance to abrasion and hydrolysis
- ✓ Resistant to most chemicals
- ✓ Very light weight and flexible



FDA Reg. Cfr.21-Item 17.2600 (aqueous and fatty food) Reg. EU 10/2011, classes A, B, C, D2



Hose & Ducting



Certificate Number: 14362
 ISO 9001



Care should be taken in selecting the most suitable quality for each application. Advice is available, but final responsibility remains with the customer.

Web: www.epdm.co.uk

E-Mail: Sales@epdm.co.uk

Contact

Telephone: +44 (0)1625 573971
 FAX: +44 (0)1625 573250
 Munsch & Co/PTM Ltd
 Units AG2/3 Clarence Mill
 Clarence Road, Bollington
 Macclesfield, Cheshire
 SK10 5JZ
 United Kingdom

Hose & Ducting

| Part number | Ø Ins. | Min. wall thick. | Max wall thick. | Weight | Vac. | Bending r. | Coil lgth. | Volume |
|--------------------|--------|------------------|-----------------|--------|------|------------|------------|----------------|
| | mm | mm | m | g/m | mH2O | mm | m | m ³ |
| EU 01 020.0 000.0 | 20 | 0,4 | 2,5 | 115 | 2,5 | 25 | 20 | 0,028 |
| EU 01 025.0 000.0 | 25 | 0,4 | 2,6 | 140 | 2,5 | 30 | 20 | 0,035 |
| EU 01 030.0 000.0 | 30 | 0,4 | 2,6 | 160 | 2,5 | 35 | 20 | 0,049 |
| EU 01 032.0 000.0 | 31,8 | 0,4 | 2,6 | 180 | 2 | 35 | 20 | 0,051 |
| EU 01 035.0 000.0 | 35 | 0,5 | 2,7 | 200 | 2 | 45 | 20 | 0,059 |
| EU 01 038.0 000.0 | 38,1 | 0,5 | 2,8 | 220 | 2 | 50 | 20 | 0,068 |
| EU 01 040.0 000.0 | 40 | 0,5 | 2,8 | 230 | 2 | 60 | 20 | 0,071 |
| EU 01 045.0 000.0 | 45 | 0,5 | 2,9 | 270 | 2 | 65 | 20 | 0,083 |
| EU 01 052.0 000.0 | 50,8 | 0,5 | 3,2 | 320 | 2 | 70 | 20 | 0,104 |
| EU 01 055.0 000.0 | 55 | 0,5 | 3,4 | 400 | 2 | 75 | 20 | 0,119 |
| EU 01 060.0 000.00 | 60 | 0,5 | 3,6 | 470 | 1,6 | 80 | 20 | 0,170 |
| EU 01 063.0 000.0 | 63,5 | 0,5 | 3,6 | 510 | 1,6 | 80 | 20 | 0,180 |
| EU 01 065.0 000.0 | 65 | 0,5 | 3,6 | 520 | 1,6 | 90 | 20 | 0,191 |
| EU 01 070.0 000.0 | 70 | 0,6 | 3,9 | 550 | 1,6 | 95 | 30 | 0,293 |
| EU 01 076.0 000.0 | 76,2 | 0,6 | 3,9 | 600 | 1,6 | 100 | 30 | 0,328 |
| EU 01 080.0 000.0 | 80 | 0,6 | 4,2 | 650 | 1,6 | 110 | 30 | 0,357 |
| EU 01 090.0 000.0 | 90 | 0,6 | 4,3 | 750 | 1,4 | 125 | 30 | 0,547 |
| EU 01 100.0 000.0 | 100 | 0,6 | 4,4 | 820 | 1,3 | 140 | 30 | 0,640 |
| EU 01 102.0 000.0 | 102 | 0,6 | 4,4 | 830 | 1,3 | 140 | 30 | 0,652 |
| EU 01 110.0 000.0 | 110 | 0,6 | 4,7 | 950 | 1,2 | 150 | 30 | 0,743 |
| EU 01 120.0 000.0 | 120 | 0,6 | 5,0 | 1100 | 1 | 160 | 30 | 0,831 |
| EU 01 127.0 000.0 | 127 | 0,6 | 5,0 | 1150 | 1 | 170 | 30 | 0,900 |
| EU 01 130.0 000.0 | 130 | 0,7 | 5,3 | 1300 | 0,9 | 170 | 20 | 0,780 |
| EU 01 140.0 000.0 | 140 | 0,7 | 5,3 | 1430 | 0,9 | 180 | 20 | 0,860 |
| EU 01 150.0 000.0 | 151,5 | 0,7 | 5,3 | 1500 | 0,8 | 200 | 20 | 0,953 |
| EU 01 160.0 000.0 | 160 | 0,7 | 6,7 | 1940 | 0,7 | 220 | 20 | 1,049 |
| EU 01 180.0 000.0 | 180 | 0,7 | 6,7 | 2140 | 0,4 | 250 | 20 | 1,236 |
| EU 01 200.0 000.0 | 200 | 0,7 | 6,7 | 2300 | 0,4 | 260 | 20 | 1,440 |
| EU 01 250.0 000.0 | 250 | 0,8 | 7,5 | 3400 | 0,4 | 300 | 10 | 0,952 |
| EU 01 300.0 000.0 | 300 | 0,8 | 7,7 | 4100 | 0,3 | 350 | 10 | 1,419 |

Also available in an Anti-static Version.



Certificate Number: 14362
 ISO 9001



Care should be taken in selecting the most suitable quality for each application. Advice is available, but final responsibility remains with the customer.

Web: www.epdm.co.uk

E-Mail: Sales@epdm.co.uk

Contact

Telephone: +44 (0)1625 573971

FAX: +44 (0)1625 573250

Munsch & Co/PTM Ltd

Units AG2/3 Clarence Mill

Clarence Road, Bollington

Macclesfield, Cheshire

SK10 5JZ

United Kingdom