

## Technical Data Sheet

### Mercury Air 20

### Premium Rubber 20 Bar Air Hose ISO2398-4A










Hose & Ducting



#### Product Information

Order Ref: RAH-SIZE MM  
 Tube: SYNTHETIC RUBBER INNER  
 Reinforcement: HIGH TENSILE SYNTHETIC TEXTILE  
 Cover: ABRASION, OZONE AND WEATHER RESISTANT SMOOTH NATURAL AND SYNTHETIC RUBBER  
 Application: MEDIUM DUTY SERVICE FOR AIR AND PNEUMATIC TOOLS SPECIFICALLY IN MINES, QUARRIES AND CONSTRUCTION

Specification: TS 745 / EN ISO 2398 TYPE 4/A

	 ID	 OD	 WP	 WP	 BP	 BP	 BR	 W/A	 COL
Inch	mm	Mm	BAR	PSI	BAR	PSI	Mm	gr/mt	Mt
1/4	6	13	20	290	60	870	60	130	25/100
5/16	8	16	20	290	60	928	80	190	25/100
3/8	10	18	20	290	60	870	100	230	25/50/100
1/2	13	22	20	290	60	870	130	333	25/50/100
3/4	19	30	20	290	60	928	190	580	25/50
1	25	36	20	290	60	870	250	730	25/50



-40°C to +70°C

Branding:

MERCURY 20 AIR/WP 20BAR ISO2398 4A-SIZE QTR/YR

Colour:

Black



Certificate Number: 14352  
 ISO 9001



Care should be taken in selecting the most suitable quality for each application. Advice is available, but final responsibility remains with the customer.

Web: [www.epdm.co.uk](http://www.epdm.co.uk)

E-Mail: [Sales@epdm.co.uk](mailto:Sales@epdm.co.uk)

#### Contact

Telephone: +44 (0)1625 573971  
 FAX: +44 (0)1625 573250  
 Munsch & Co/PTM Ltd  
 Units AG2/3 Clarence Mill  
 Clarence Road, Bollington  
 Macclesfield, Cheshire  
 SK10 5JZ  
 United Kingdom