

Technical Data Sheet

Neoduct 1S

Product Information



Wall: One ply of Neoprene coated glass -fibre fabric, single outer glass cord
 Spiral: Spring Steel Wire
 Application: Industrial ventilation systems
 Welding Gases, Furnace Exhaust,

Hose & Ducting

Part number	Inside Ø mm	WP Bar	Vacuum m H2O	Bending R. Mm	Weight kg/m	Length m
P801019	19	1.5	5.3	9	0.08	4
P801022	22	1.5	5.3	11	0.08	4
P801025	25	1.4	5.3	12	0.12	4
P801032	32	1.4	5	16	0.13	4
P801038	38	1.4	5	19	0.16	4
P801041	41	1.3	4.5	21	0.17	4
P801044	44	1.2	4.4	22	0.19	4
P801051	51	1.2	4.4	25	0.25	4
P801057	57	1.1	4	28	0.28	4
P801063	63	1.1	4	31	0.3	4
P801070	70	1.1	3.5	35	0.39	4
P801076	76	1	3.5	38	0.41	4
P801083	83	1	3	41	0.47	4
P801089	89	0.9	2.95	44	0.49	4
P801095	95	0.9	2.7	47	0.54	4
P801102	102	0.9	2.6	51	0.57	4
P801108	108	0.8	2.3	54	0.68	4
P801114	114	0.8	2.1	57	0.73	4
P801121	121	0.8	1.9	60	0.76	4
P801127	127	0.8	1.7	63	0.8	4
P801140	140	0.8	1.5	70	0.88	4
P801152	152	0.6	1.4	76	1.05	4
P801160	160	0.6	1.2	80	1.09	4
P801178	178	0.6	1	89	1.21	4
P801203	203	0.5	0.7	101	1.38	4
P801229	229	0.4	0.6	114	1.49	4
P801254	254	0.4	0.5	127	1.65	4
P801305	305	0.1	0.3	152	2	4



Certificate Number: 14352
 ISO 9001



Care should be taken in selecting the most suitable quality for each application. Advice is available, but final responsibility remains with the customer.

Web: www.epdm.co.uk

E-Mail: Sales@epdm.co.uk

Contact

Telephone: +44 (0)1625 573971
 FAX: +44 (0)1625 573250
 Munsch & Co/PTM Ltd
 Units AG2/3 Clarence Mill
 Clarence Road, Bollington
 Macclesfield, Cheshire
 SK10 5JZ
 United Kingdom