

Technical Data Sheet

Silduct 2S

Wall: 2 ply's of silicone coated glass -fibre fabric, double outer glass cord
Spiral: spring steel wire

For Medium and High Temperature use in welding, plastics, smoke, vapour or ventilation environments.

Hose & Ducting



Certificate Number: 14362
ISO 9001



Care should be taken in selecting the most suitable quality for each application. Advice is available, but final responsibility remains with the customer.

Web: www.epdm.co.uk

E-Mail: Sales@epdm.co.uk

Contact

Telephone: +44 (0)1625 573971

FAX: +44 (0)1625 573250

Munsch & Co/PTM Ltd

Units AG2/3 Clarence Mill

Clarence Road, Bollington

Macclesfield, Cheshire

SK10 5JZ

United Kingdom

Hose & Ducting

Part number	Inside Ø m m	WP bar	Vacuum mH ² O	Bending R. mm	Weight kg/m	Length m
P435019	19	2.5	7	12	0.1	4
P435022	22	2.5	7	14	0.13	4
P435025	25	2.5	7	15	0.14	4
P435032	32	2.5	5.8	16	0.18	4
P435038	38	2.4	5.8	18	0.21	4
P435041	41	2.4	5.8	19	0.23	4
P435044	44	2.4	5.8	21	0.25	4
P435051	51	2.4	5.3	24	0.28	4
P435057	57	2.3	5.3	28	0.33	4
P435063	63	2.2	4.6	31	0.35	4
P435070	70	2.2	4.6	35	0.43	4
P435076	76	2.1	4.4	39	0.47	4
P435083	83	2.1	4	42	0.51	4
P435089	89	2.1	4	44	0.54	4
P435095	95	2	4	49	0.57	4
P435102	102	1.8	3.5	52	0.61	4
P435108	108	1.8	3	54	0.73	4
P435114	114	1.7	2.8	58	0.78	4
P435121	121	1.6	2.3	61	0.81	4
P435127	127	1.5	2.1	64	0.86	4
P435140	140	1.4	1.8	69	0.94	4
P435152	152	1.1	1.7	75	1.1	4
P435160	160	0.9	1.5	80	1.14	4
P435178	178	0.8	1.4	90	1.27	4
P435203	203	0.6	1	101	1.39	4
P435229	229	0.5	0.8	127	1.6	4
P435254	254	0.4	0.7	150	1.78	4
P435305	305	0.2	0.5	210	2.17	4



Certificate Number: 14362
 ISO 9001



Care should be taken in selecting the most suitable quality for each application. Advice is available, but final responsibility remains with the customer.

Web: www.epdm.co.uk

E-Mail: Sales@epdm.co.uk

Contact

Telephone: +44 (0)1625 573971

FAX: +44 (0)1625 573250

Munsch & Co/PTM Ltd

Units AG2/3 Clarence Mill

Clarence Road, Bollington

Macclesfield, Cheshire

SK10 5JZ

United Kingdom