

Technical Data Sheet


Statite Oil Paper (WCMSTATITE)

DESCRIPTION:

Plasticised gelatine impregnated material, cellulose based

PHYSICAL PROPERTIES

TENSILE STRENGTH:	13.0 N/mm ²
COMPRESSIBILITY:	12-16%
THICKNESS:	±10%
RECOVERY:	25 - 40%
MAXIMUM TEMPERATURE:	120°C Recommended
MAXIMUM PRESSURE:	8 Bar
IRM903 OIL WEIGHT INCREASE:	<15%
IRM903 OIL THICKNESS INCREASE:	<5%
FUEL B WEIGHT INCREASE:	<15%
FUEL B THICKNESS INCREASE:	<5%
WATER WEIGHT INCREASE:	<90%
WATER THICKNESS INCREASE:	<30%



GASKET PAPER

Statite is a very economical gasket/oil paper. It's price factor is important when dealing with original equipment and replacement markets. The material has excellent oil and fuel resistance

Its prime market is automotive but it has limited uses in industrial markets because of relatively low heat and chemical resistance compared with non-asbestos materials.

Care should be taken in selecting the most suitable quality for each application. Advice is available, but final responsibility remains with the customer.

www.epdm.co.uk

E-Mail: Sales@epdm.co.uk

Contact

Telephone: +44 (0)1625 573971
 FAX: +44 (0)1625 573250
 Munsch & Co/PTM Ltd
 Units AG2/3 Clarence Mill
 Clarence Road, Bollington
 Macclesfield, Cheshire
 SK10 5JZ
 United Kingdom



Certificate Number: 14352
 ISO 9001

